

The industry proven **QuickJack™ Classic**, which is based on the Wincor platform is designed to easily integrate with any host slot ticket Management system. It's the ideal solution for casinos who are looking to enhance and Improve customer service on the gaming floor.

FEATURES

STANDARD

- 12" colour VGA monitor
- 3 high capacity coin hoppers
- 4 programmable cash cassettes
- 2 JCM bill validators
- Thermal receipt printer
- Illuminated entry/exit points
- 8 stainless steel function keys c/w Braille
- Lockable reject bin
- DIP Card reader
- Triple DES encrypted pin pad

APPLICATIONS

- Ticket-in, ticket-out (TITO) ticket redemption, which interfaces to all major slot ticket systems
- Bill-breaking
- ATM functionality with the PLUS and CIRRUS networks
- Player points redemption
- Jackpot redemption
- Currency exchange
- Ballot production
- Parking redemption
- Wager account transfer (WAT)
- E-coupon redemption

QuickJack™ Classic



Available as an option 22" multimedia display.

QuickJack™
Classic

SPECIFICATIONS



FEATURES

- 12" VGA monitor
- 3 high capacity coin hoppers
- 4 programmable cash cassettes
- 2 JCM bill validators
- Thermal receipt printer
- Illuminated entry/exit points
- 8 stainless steel function keys c/w Braille
- Sealable reject bin
- ID-Card reader DIP
- Illuminated candle
- Pull out components for service
- Uninterruptable power supply
- Best in class ergonomics & design

SECURE SYSTEM

- Secure CHS Backoffice
- Electronic Journaling
- Bank certified ATM software
- Audit Log files
- Automatic device diagnostics
- Sensitive data encryption
- Multi-level password control
- UL-291
- Security camera (Optional)
- PCI Compliant

DIMENSIONS

- Width: 30"
- Height: 55"
- Depth: 27.5"
- Candle: 3.5"
- Foot print: 5.7 sq.ft
- Weight: 980lbs. (445 kg)

COMPLIANCE

- ADA/ADAAG compliant
(Americans with Disability Act)
- ADS3769-1990 Australian
- UK Design Guidelines
- CAN/CSA B651.1-01
- RoHS
(Restriction of Hazardous Substances)

POWER REQUIREMENTS

- Line Voltage: 110-120v/220-240v
- Rated Frequency: 50/60Hz

ENVIRONMENTAL

- Ambient Temperature: +15 to +35 C
- Relative Humidity: 5% to 85%

CORPORATE HEAD OFFICE

NRT Technology Corp.

10 Compass Court, Toronto, ON Canada M1S 5R3

Within Canada: Toll Free (800) 363-1671

Within USA: Toll Free (866) 230-8425

Tel. (416) 646-5232 **Fax** (416) 646-5242

U.S. OFFICE

NRT Technology Corp.

6380 S. Valley View Blvd., Suite 420

Las Vegas, Nevada USA 89118

Toll Free (866) 430-7630

Tel. (702) 407-7630 **Fax** (702) 407-7625

ASIA PACIFIC

NRT Technology Corp.

335 Alameda Dr. Carlos d'Assumpcao,

Edificio "Hot Line" 17th Floor "V"

Macau (SAR), China

Tel. (853) 2875-2305 **Fax** (853) 2875-2310



WWW.NRTTECH.COM